

EAST - [09505645.wsp:1]

File View Edit Tools Window Help

☒ L11: (5) bias adj1 charge same capacitor same photodiode  
☒ L12: (1) "6693673"  
☒ L13: (498) (different or variable) near3 integration near3  
☒ L14: (78) 348/\$.cc1s. and (different or variable) near3  
☒ Failed  
☒ Saved  
☒ (0) oversaturated same pixel same reset same brightness  
☒ (0) oversaturated same pixel same brightness

Search List Browse Queue Clear  
DBs USPAT ☒ Plurals  
Default operator: OR ☒ Highlight all hit terms initially  
348/\$.cc1s. and (different or variable) near3  
integration near3 time  
BRS f... IS&R... Image Text HTML

	U	1	Document ID	Issue Date	Pages	Title	Current OR	Current XRef
1	<input type="checkbox"/>	<input type="checkbox"/>	US 6714239 B2	20040330	18	Active pixel sensor with programmable color balance	348/223.1	348/280; 348/297;
2	<input type="checkbox"/>	<input type="checkbox"/>	US 6710804 B1	20040323	12	CMOS active pixel image sensor with extended dynamic range and	348/302	257/233; 348/275
3	<input type="checkbox"/>	<input type="checkbox"/>	US 6665010 B1	20031216	13	Controlling integration times of pixel sensors	348/297	348/301; 348/308;
4	<input type="checkbox"/>	<input type="checkbox"/>	US 6657177 B2	20031202	19	Solid-state imaging system	250/208.1	348/302
5	<input type="checkbox"/>	<input type="checkbox"/>	US 6606123 B2	20030812	15	Photosensitive device	348/308	
6	<input type="checkbox"/>	<input type="checkbox"/>	US 6576882 B2	20030610	12	Image sensor	250/208.1	348/308
7	<input type="checkbox"/>	<input type="checkbox"/>	US 6573935 B1	20030603	16	Two-dimensional solid state image pickup device	348/272	348/280; 348/297
8	<input type="checkbox"/>	<input type="checkbox"/>	US 6563540 B2	20030513	15	Light sensor with increased dynamic range	348/302	257/291; 348/308
9	<input type="checkbox"/>	<input type="checkbox"/>	US 6542189 B1	20030401	14	Frequency compensated multiple sampling method for a video digital	348/297	348/364
10	<input type="checkbox"/>	<input type="checkbox"/>	US 6529242 B1	20030304	16	Look ahead shutter pointer allowing real time exposure control	348/308	348/362
11	<input type="checkbox"/>	<input type="checkbox"/>	US 6529241 B1	20030304	13	Photodetecting device supporting	348/308	250/208.1;

Hits Details HTML

Ready NUM

- ☐ Drafts
- ☐ Pending
- ☒ Active
  - ☒ L1: (104) 348/\$.cccls. and non adj1 destructive near3 rea
  - ☒ L2: (97) 348/\$.cccls. and non adj1 destructive near2 read
  - ☒ L3: (19) 348/\$.cccls. and non adj1 destructive adj1 readi
  - ☒ L4: (6) ("4471228" | "4544848" | "5038214" | "5264940" |
- ☐ Failed
- ☒ Saved

☐ Plurals

Default operator: 
☒ Highlight all hit terms initially

	U	1	Document ID	Issue Date	Pages	Title	Current OR	Current XRef
1	<input type="checkbox"/>	<input type="checkbox"/>	US 6219097 B1	20010417	22	Image pickup with expanded dynamic range where the first exposure is	348/297	348/362; 348/364
2	<input type="checkbox"/>	<input type="checkbox"/>	US 6166768 A	20001226	18	Active pixel sensor array with simple floating gate pixels	348/308	257/E27.132; 257/E27.133;
3	<input type="checkbox"/>	<input type="checkbox"/>	US 6124888 A	20000926	46	Image pickup apparatus capable of reading in optional reading mode	348/302	348/308
4	<input type="checkbox"/>	<input type="checkbox"/>	US 5717199 A	19980210	13	Collective charge reading and injection in random access charge	250/208.1	348/306; 348/308
5	<input type="checkbox"/>	<input type="checkbox"/>	US 5650643 A	19970722	7	Device for receiving light used in CCD image sensor or the like	257/225	257/222; 257/228;
6	<input type="checkbox"/>	<input type="checkbox"/>	US 5414464 A	19950509	11	Image sensor and electronic still camera with an addressable image	348/222.1	348/231.99; 358/909.1
7	<input type="checkbox"/>	<input type="checkbox"/>	US 5153713 A	19921006	28	Color temperature information forming device	348/655	348/656
8	<input type="checkbox"/>	<input type="checkbox"/>	US 5018006 A	19910521	35	Multi-plate type image pickup apparatus having picture elements	348/275	348/276; 348/281
9	<input type="checkbox"/>	<input type="checkbox"/>	US 4972243 A	19901120	13	Photoelectric conversion apparatus with shielded cell	257/435	250/204; 250/214.1;
10	<input type="checkbox"/>	<input type="checkbox"/>	US 4907074 A	19900306	34	Image pickup apparatus having color separation filters and forming	348/237	348/276